

# Manifest



Vi tror på at lys er mere end blot oplysning af byrum og private hjem.

Vi tror på lysets evne til at forundre, bringe glæde og skabe minder.

Når vi udvikler og designer vores belysning, indarbejder vi disse værdier i enhver detalje.

Vi sætter en dyd i at producere kvalitetsprodukter, der tager hensyn til både miljø og mennesker.

Goodwill og en etisk tilgang er grundstenen for vores virksomheds værdier, og kan ses i alle vores projekter over hele verden.

Vi er Blachere og vi har produceret lys og lysinstallationer med ansvar og passion i 45 år.



Vi mener at jul- og vinterbelysning gjør langt mer enn å lyse opp våre byer og tettsteder.

Vi tror på lysets evne å overraske, skape glede og få fram eventyrstemning. Vi designet og utvikler produkter som gjenspeiler alt dette ned til minste detalj.

Vi bestreber oss på god kvalitet i alle våre produkter og vi gjør vårt ytterste for å ivareta miljø og humanitært arbeid.

Bærekraft og etikk er hjertet i vår bedriftskultur og manifesterer seg i alle våre prosjekter rundt om i verden.

Vi er Blachere og har produsert belysning med omtanke og lidenskap i 45 år.



Uskomme että valaistuksen avulla voi urbaaniin kulttuuriin ja elinympäristöön tuoda muutakin kuin valoa: Me uskomme ihmeen voimaan, satumaailmojen luomiseen ja niiden valaisuun.

Kaikki nämä asiat sisältyvät tapaan, jolla me suunnittemme ja kehitämme valaistuksiamme.

Me olemme sitoutuneet valmistamaan laadukkaita tuotteita, unohtamatta ympäristövällisyttä ja ihmillisyyttä.

Sekä liiketaloudellinen että eettinen lähestymistapa on toimintamme perusajatuksia ja nähtävissä eri projekteissamme ympäri maailman.

Me olemme Blachere illumination ja olemme tuottaneet valaistuksia huolella ja intohimoisesti jo 45 vuotta.



Vi tror att belysning ger mer än bara ljus till stads – och bostadsområden.

Vi tror på dess förmåga att förundra, att lysa upp och att berätta sagor.

Vi skapar och uppfinner utifrån era projekt och genomarbetar varje detalj så att resultatet skall motsvara era förväntningar.

Vi är fast beslutna att tillverka kvalitetsprodukter med hänsyn till miljön och framtida generationer.

Generositet och etik är kärnan i vår kultur som återfinns i alla våra projekt över hela världen.

Vi på Blachere har tillverkat belysningar med omsorg och passion i 45 år.

# What inspires us

In 1973, Jean-Paul Blachère invented a signature profession that lights up living spaces and cities.

Today, we are more than 400 people all around the world committed to change everyday life for the better.

Whether designed for capitals, villages, cities, shopping centers, parks, monuments etc. our projects reflect our creativity and our ability to invent increasingly innovative decorations and solutions.

We want to create beautiful pieces all over the world, for sure, but keeping in mind one of our top priorities: eco-responsibility. Half of our research and development budget is allocated to ecoresponsible innovations.

We make every effort to limit the impact of our products to protect the planet and this marks just the beginning of our pursuit of eco-responsibility.





5

## Our network

Blachere illuminates the world thanks to its 28 subsidiaries.  
Each country has its own traditions and culture.

For us, learning about the DNA of each place and respecting it is vital,  
to best carry out, not only magnificent, but coherent projects.  
For the stakes and desires are not the same in Mexico, Sweden or  
Germany, we match each challenge with the perfect team to help  
you set up illuminations from the first contact.  
Whether enhancing historic monuments, illuminating an avenue,  
transforming a majestic fountain or decorating a village square in  
Paris, Moscow or London, we aim to glorify places while respecting  
their history.

**65%** of french towns  
illuminated

**1000** cities worldwide in more  
than 150 countries

**17** of the 20  
largest cities in France

**500** shopping centres  
decorated worldwide

# Sustainability

Our commitment to protect the planet isn't just something we talk about. It's been in our DNA for over 10 years.

So, it was only natural that we take the same eco-friendly approach for our clients when creating new solutions for them. Having been the first to make LEDs the norm, we are now revolutionising our illuminations' structural design thanks to our eco-responsible and recyclable materials. With Bioprint – that comes from sugar cane – and Recyprint – designed with recycled plastic bottles – we can remove over 80% of the aluminium from our 2D decorations (more info p.12 to 17).

We also have our NORDIKA tree which looks just like a real Christmas tree but avoids deforestation (see p.38 to 43) and ORCHESTRA: the app that allows for smart, optimized illumination and electricity management (contact us for more informaitons).

Common sense and compassion also underpin how we behave as a business as we aim to significantly and sustainably reduce our carbon footprint.

We are taking action in this area including making our communication tools paperless wherever possible, recycling our waste, generating green energy at our wind farm, installing solar panels and replacing our fleet with hybrid vehicles.

We are also involved in the process of obtaining ISO 14001 certification.





# Interactivity

Our goals: amaze, surprise, touch hearts. More than just illuminations, we offer solutions to make our decorations more and more lively and interactive.

Everything is thought of to make the visitor feel completely involved: he/she can change the color of the decorations, add augmented reality for unforgettable photos. We have developed a range of interactive products and mobile apps to use in towns, cities or shopping centers to entertain, make a big impression and leave the public wanting to extend their visit and return.

Interactivity is even more attractive than illuminations. It brings generations together to share a unique experience as the public stop being onlookers and become involved.

# Expertise

We are very fond of our wonderful region, Provence, here in France.

60 staff members work in our «haute couture» workshops in Apt, and more than 120 during high season. Every year, they produce more than 6000 custom-made decorations: giant fir trees over 25 meters long, monumental fountains or multicolored tunnels of 100 meters long. All requiring skills in ironwork and in the most complex cabling.

A total of 50,000 decorations are manufactured each year at our production sites.

Because our imagination holds no bounds and 'know-how' is our specialty, feel free to contact us regarding any unique decoration project tailored from start to finish:

Extraordinary decorative fir tree, disproportionate size, custom design, multicolored animation, the possibilities are endless.

An international team of over 30 designers create our vast range of decorations: everything from transverses above the streets, to spectacular facade decor for major stores and fun 3D characters.

We start each project with a clean slate and create motifs and designs to suit our clients' wishes.

We renew every year more than half of the decorations displayed in this catalogue according to the latest international trends and influences.

The government has awarded us the French EPV label which singles out French companies with artisan and industrial know-how exporting abroad.

We are the only French company specialized in illumination to have obtained ISO 9001 certification.



# Our range of ecoresponsible decorations

**Protecting the planet: not just an option – our duty.**

Our R&D department is constantly looking for ethical materials for the design of our structures. Having been the first to make LEDs the norm, to recycle our garlands and revolutionize our illuminations thanks to BioPrint – a recyclable and biodegradable material – we are now innovating by launching Recyprint, a range of decorations designed from plastic bottles.

## The eco-design of our decorations as a priority.

Our 2D decorations are equipped with a recycled and recyclable aluminium frame designed to support the structure and printed with our wide-format printers in Bioprint or Recyprint. The 100% LED lighting components are recycled after use and are all interconnected with the Octoplus system. These brand new eco-responsible materials allow us to remove more than 80% of aluminium from our 2D motifs, which has a substantial impact on our carbon footprint.

**Indeed, our Bioprint or Recyprint manufacturing process emits 10 times less CO2 than aluminium.**

Eco-responsibility is at the heart of our strategy. Now and more than ever. And we are committed to constantly thinking about innovations and ethical materials to create beautiful and magical things, while protecting the planet and people.



## BIOPRINT ou RECYPRINT RECYCLABLE STRUCTURE

The lighting components are wired onto a structure entirely made from our revolutionary new eco-responsible materials, available in different colours.



## RECYCLED ALUMINIUM FRAME

We use this aluminium frame and its sleek design to support the **Bioprint** structure. The aluminium used to manufacture all of our decorations is then collected and processed by a certified body.


## OCTOPLUS INTERCONNECTIVITY

The optimization of the interconnectivity between our different lighting components allows a multitude of assemblies while limiting the number of connection accessories.

## RECYCLED ELECTRIC COMPONENTS

ECOSYSTEM – an eco-organization approved for the process of professional WEEE (Waste Electronic and Electrical Equipment) – collect and recycle all our garlands and other electrical components used for decorations.

**ecosystem**



# Bioprint

A recyclable and biodegradable biomaterial made from sugar cane

Bioprint designs are made from biosourced GMO-free sugar cane which is turned into dehydrated bioethanol at a French laboratory. When the granules arrive at our workshops in Apt, France, they are dyed with our own colours. The material is then injected into our 3D printers which produce colourful, biodegradable and recyclable structures.

A process that reduces the waste at the manufacturing stage and allows total recyclability at the end of its life..

"Biodegradation" means the decomposition of organic matter by microorganisms, with no harmful effect on the natural environment.

Our decorations biodegrade slowly at the end of their life - they can be installed outdoors for long periods without causing aesthetic or mechanical damage. One advantage of this slowness is that it minimises the greenhouse gases generated when the complex molecules that make up our revolutionary material biodegrade.

While industrial composting is one way to sensibly manage this biomass, the ecofriendliest approach is to recycle the material. By doing this, daily waste production can be minimised.



RECYCLABLE &  
BIODEGRADABLE



ORGANICALLY  
SOURCED



CERTIFIED AS  
GMO-FREE



IK10      UV  
RESISTANCE

# Recyprint

Less plastic bottles  
for a clean planet



► 500 billion bottles are produced every year and many of them end up being littered or in the oceans.

At Blachere, we have decided to tackle the scourge of plastic pollution by recycling PET (polyethylene terephthalate) from the food industry to create beautiful and innovative decorations using this unique material - rPET (recycled PET).

Indeed, each year, about 8 million tons of waste end up in the oceans and form the 7th continent - a vortex of floating plastics equivalent in size to 1/3 of Europe.

**Recycling, creating, innovating.**

The bottles we salvage are sorted by colour (from colourless to blue), then crushed into flakes to be shaped for extrusion. The granules resulting from this transformation are then injected into our 3D printers to create unique blue decorations.

This unrivalled method helps to limit greenhouse gas emissions and to keep our nature clean from plastic bottles as far as possible.



8 recycled plastic bottles are needed to create one flake of 80 cm.



RECYCLABLE



TOTAL CIRCULAR ECONOMY  
NO MATERIAL CREATED



LOCAL SUPPLY  
IN rPET





Oslo - Norway



Langesund - Norway

22



23





Rewell center – Vaasa – Finland



Rewell center – Vaasa – Finland

26



Helsinki - Finland

27



Aalborg city - Denmark

28



Malmö - Sweden

29



Redi - Helsinki - Finland



Skulpturparken Blockhus - Denmark



Kamppi SC - Helsinki - Finland

32



Gjøvik - Norway

33



Mosseporten - Moss - Norway

34



Superbrugsen - Galten - Denmark

35



Stureplan - Stockholm - Sweden



range

# Green

---

This sweet and gentle collection combines tradition and a sense of poetry to warm up Christmas with its warm white and green hues. Arabesques, bows and delicate ropes light up the streets of towns and cities to provide a romantic feel.

# Nordika

The christmas tree  
better than a real one!

Who hasn't dreamt of a huge Christmas tree? However, a natural tree takes 30 or 40 years to reach a height of 12 m. To avoid being involved in deforestation and cutting down these majestic four-decades-old trees, we have invented Nordika. Pre-illuminated with a SlowGlow effect, and easy to put up and store away, they are perfect replicas of their natural cousins thanks to their design and incredibly realistic look.

**Our eco-designed Nordika range**

We have based our environmental approach on a simple principle: saving at least as much carbon emissions as released. To do so, we use only biocompatible materials that we recycle at the end of their life. We are also putting our best efforts to reduce the carbon dioxide emissions in our own production and those of our stakeholders.



OPTIONAL  
TREETOP



HYPER REALISTIC  
CHRISTMAS TREE  
BRANCHES



WOOD-EFFECT TRUNK



WOOD EFFECT  
STAND AVAILABLE



# The Christmas tradition

What could be more iconic than a majestic Christmas tree during the holiday season? This Christmas, Blachère has reinvented this festive classic, taking care of every little detail: The perfectly regular branches, realistic high-quality finish and majestic size make this a must-have product.

Just as you carefully consider how you will decorate your Christmas tree at home each year to surprise and amaze your family and friends, you can personalise your Nordika to make it unique: hang baubles from the branches, add lit toppers, or put them in a wooden stand.

Our NORDIKA tree remains a lasting, high-quality investment in line with the very best of Christmas tradition.

New construction:  
8 additional branches



| Ref       | Name               | Height  | $\varnothing$ | P(W)   | Weight   | No of elements | Colour of Led | No of Led   |
|-----------|--------------------|---------|---------------|--------|----------|----------------|---------------|---|
| GX081LW-2 | sapin Nordika - PM | 5,00 m  | 3,56 m        | 245 W  | 263 kg   | 46             | ●             | 2976 (1488 steady + 1488 with slowglow effect)    |
| GX082LW   | sapin Nordika - MM | 8,00 m  | 4,70 m        | 770 W  | 1112 kg  | 107            | ●             | 8664 (4332 steady + 4332 with slowglow effect)    |
| GX083LW   | sapin Nordika - GM | 12,00 m | 5,90 m        | 1870 W | 2 750 kg | 194            | ●             | 21048 (10524 steady + 10524 with slowglow effect) |



## Accessories for Nordika and trees

### Decorative baubles kit

Each kit features 52 baubles in the same colour (M1/B1 category - fireproof) - 50% shiny / 50% satiny

- 28 baubles ø 12cm
- 20 baubles ø 20cm
- 4 baubles ø 25cm



| Nordika tree         | 5m     | 8m     | 12m    |
|----------------------|--------|--------|--------|
| Kits number          | 2 kits | 4 kits | 8 kits |
| Baubles total number | 104    | 208    | 416    |

| Colour | Reference |
|--------|-----------|
| Silver | KITNDK-A  |
| Blue   | KITNDK-B  |
| Gold   | KITNDK-O  |
| Red    | KITNDK-R  |

### Base and tree topper

4 tree toppers are available for an additional magical touch to your Nordika tree.

Bases can also be featured with all Nordika trees.



| Tree topper     | ø     | Reference |
|-----------------|-------|-----------|
| cimier star7    | 0.80m | CIME7     |
| cimier bella    | 1.00m | CIME2     |
| cimier mia      | 1.00m | CIME6     |
| cimier aiguille | 1.00m | CIME4     |

| Base                        | Reference |
|-----------------------------|-----------|
| Nordika base 5m (GX081LW-2) | SOCLGX81  |
| Nordika base 8m (GX082LW)   | SOCLGX82  |
| Nordika base 12m (GX083LW)  | SOCLGX83  |





● TL341W  
◆ 1.50m - ◆ 6.00m  
⚡ 110W - ☉ 28.0kg



● ITL114W  
◆ 0.90m - ◆ 4.00m  
⚡ 150W - ☉ 18.6kg



● ITL113W  
◆ 0.70m - ◆ 4.00m  
⚡ 152W - ☉ 25.0kg



● PL346W + ● GX048LW  
◆ 2.50m - ◆ 1.42m ◆ 0.73m - ⌀ 0.48m  
⚡ 23W - ☉ 16.0kg ⚡ 40W - ☉ 4.3kg



● IPL114W  
◆ 2.00m - ◆ 0.90m  
⚡ 65W - ☉ 9.3kg



● IPL113W  
◆ 2.00m - ◆ 0.70m  
⚡ 55W - ☉ 7.8kg



● PL313W + ● GX116LW  
◆ 2.00m - ◆ 1.00m ◆ 0.70m - ◆ 0.60m  
⚡ 20W - ☉ 10.8kg ⚡ 15W - ☉ 3.0kg




● PL312W  
◆ 1.60m - ◆ 0.90m  
⚡ 53W - ☉ 12.0kg



● PL344W  
◆ 0.60m - ◆ 0.95m  
⚡ 10W - ☉ 5.2kg  
● PL344

PL313W and PL346W : Optional hanging motif.

Detailed technical information p140 to 144



● **GX117LW**  
 ◆ 2,00m - ◆ 1,50m - ■ 1,50m  
 ✎ 126W - ✎ 33kg



● **PL345**  
 ◆ 1,30m - ◆ 1,00m  
 ✎ 10W - ✎ 5,9kg



● **GX048LW**  
 ◆ 0,73m - ◆ 0,48m - ■ 0,48m  
 ✎ 40W - ✎ 4,3kg



● **GX116LW**  
 ◆ 0,70m - ◆ 0,60m  
 ✎ 15W - ✎ 3,0kg



● **FCL080G-E**  
 ◆ 0,80m - ◆ 0,80m - ■ 0,80m  
 ✎ 15W - ✎ 3,62kg  
 ● **FCL080A-E**

## Composition ideas



Detailed technical information p140 to 144

## Composition ideas



Detailed technical information p140 to 144

**N**

| Description                     | Height  | $\varnothing$ | P(W)  | Weight  | Parts number | ○               | ●                |
|---------------------------------|---------|---------------|-------|---------|--------------|-----------------|------------------|
| Conical fir tree 3m             | 3,00 m  | 1,18 m        | 24 W  | 41 kg   | 3            | <b>SV301</b>    | <b>SV301W</b>    |
| Conical fir tree 5m             | 5,00 m  | 1,80 m        | 60 W  | 250 kg  | 6            | <b>SV501</b>    | <b>SV501W</b>    |
| Conical fir tree 10m            | 10,00 m | 3,43 m        | 248 W | 965 kg  | 23           | <b>SV1001</b>   | <b>SV1001W</b>   |
| Conical fir tree 14m            | 14,36 m | 5,80 m        | 640 W | 4462 kg | 49           | <b>SV1401</b>   | <b>SV1401W</b>   |
| Conical "crossing" fir tree 8m  | 8,00 m  | 2,78 m        | 200 W | 615 kg  | 17           | <b>SV801-P</b>  | <b>SV801W-P</b>  |
| Conical "crossing" fir tree 12m | 12,00 m | 4,08 m        | 440 W | 1427 kg | 33           | <b>SV1201-P</b> | <b>SV1201W-P</b> |

Decorative baubles not included - Decorating suggestion - Our decorative baubles kits are presented p43.



● **GX057LW**

◆ 2,50m - ◆ 1,60m - ■ 1,60m  
↳ 40W - ↳ 53,0kg

GX057LW: Passive balls not included

● **GX058LW**

◆ 2,10m - ◆ 0,48m - ■ 0,24m  
↳ 15W - ↳ 31kg

● **GX059LW**

◆ 3,00m - ◆ 0,80m - ■ 0,40m  
↳ 24W - ↳ 32kg

Detailed technical information p140 to 144



Detailed technical information p140 to 144



Detailed technical information p140 to 144



60

61


Frozen range

range

# Frozen

---

The north wind blows its frosty air and star-shaped snowflakes fall in their thousands. You can find all the magic of these gorgeous snow crystals in our decorations which create a magical polar atmosphere in white, gold and blue tones.



Easily transform any hanging decoration into a polemount decoration, thanks to our accessory: PIX01

Detailed technical information p140 to 144



Detailed technical information p140 to 144



range

# Ribbon & sphere

---

Shooting stars, baubles, gifts... This decidedly joyful and colourful collection will provide an imaginative Christmassy touch, decorating streets, building frontages and landmarks to create a brightly lit panorama that is dazzling and magical.

# Trondheim Torg

*God Jul*



● ITL044W-S  
◆ 1.42m - ◆ 4.65m  
⚡ 115W - ⚡ 19.6kg



● IPL039W-S  
◆ 2.00m - ◆ 0.72m  
⚡ 35W - ⚡ 6.2kg



*God Jul*  
*Gladlyig Jul*  
*Hyvä Joulua*  
*Valkomme til jul!*

● ITL062W-S  
◆ 1.50m - ◆ 5.00m  
⚡ 116W - ⚡ 22.0kg

● ITL064W-S  
◆ 1.00m - ◆ 3.50m  
⚡ 114W - ⚡ 23.0kg

● ITL063W-S  
◆ 1.20m - ◆ 6.00m  
⚡ 210W - ⚡ 37.0kg

● ITL116W  
◆ 1.18m - ◆ 6.00m  
⚡ 168W - ⚡ 27.0kg




Detailed technical information p140 to 144

# Bioprint ceiling lights in 3D




| Reference | Description | Colour | Height | Width | Depth | P(W) | Weight |
|-----------|-------------|--------|--------|-------|-------|------|--------|
| ITGL102   | diams       | ○      | 0,60m  | 0,40m | 0,24m | 16W  | 4,0kg  |
| ITGL102W  | diams       | ●      | 0,60m  | 0,40m | 0,24m | 16W  | 4,0kg  |
| ITGL109   | star5       | ○      | 0,50m  | 0,50m | 0,12m | 8W   | 2,0kg  |
| ITGL109W  | star5       | ●      | 0,50m  | 0,50m | 0,12m | 8W   | 2,0kg  |
| ITGL111   | star7       | ○      | 0,80m  | 0,80m | 0,18m | 16W  | 4,0kg  |
| ITGL111W  | star7       | ●      | 0,80m  | 0,80m | 0,18m | 16W  | 4,0kg  |

Detailed technical information p140 to 144



Schematic diagram of all the ceiling lights presented on this double page:



Easily transform any hanging decoration into a polemount decoration, thanks to our accessory: PIX01.

| Reference | Description   | Colour | Height | Width | Depth | P(W) | Weight |
|-----------|---------------|--------|--------|-------|-------|------|--------|
| ITGL107   | sphere frozen | ○      | 0,50m  | 0,50m | 0,26m | 22W  | 4,0kg  |
| ITGL108   | sphere frozen | ○      | 0,80m  | 0,80m | 0,40m | 44W  | 8,0kg  |
| ITGL104   | sphere full   | ○      | 0,50m  | 0,50m | 0,26m | 22W  | 4,0kg  |
| ITGL104W  | sphere full   | ●      | 0,50m  | 0,50m | 0,26m | 22W  | 4,0kg  |
| ITGL105   | sphere full   | ○      | 0,80m  | 0,80m | 0,40m | 44W  | 8,0kg  |
| ITGL105W  | sphere full   | ●      | 0,80m  | 0,80m | 0,40m | 44W  | 8,0kg  |
| ITGL117R  | love          | ●      | 0,60m  | 0,60m | 0,46m | 8W   | 2,0kg  |

Detailed technical information p140 to 144



# 3D Characters & animals

---

Each year, we design 3D characters to create exciting, fun and joyful decorations.

From a funny bear to a majestic deer or a giant Father Christmas, all our creations make a wonderful spectacle for all ages. They are mostly interactive and animated (ending in -A references).



**GX194L**  
◆ 1,20m - ◆ 2,30m - ■ 1,20m  
◆ 79W - ■ 82,0kg

**GX092L**  
◆ 2,20m - ◆ 1,15m - ■ 0,70m  
◆ 22W - ■ 30,0kg

**GX093L**  
◆ 2,00m - ◆ 1,20m - ■ 0,60m  
◆ 22W - ■ 22,0kg



**GX042L**  
◆ 2,20m - ◆ 1,20m - ■ 0,80m  
◆ 18W - ■ 39,0kg

**GX132L**  
◆ 3,60m - ◆ 2,60m - ■ 1,90m  
◆ 101W - ■ 96,0kg

**GX104L-S**  
◆ 2,15m - ◆ 0,96m - ■ 0,85m  
◆ 62W - ■ 30,0kg



**GX097L**  
◆ 2,00m - ◆ 1,30m - ■ 0,60m  
⌚ 24W - ☈ 31,0kg

**GX130L**  
◆ 1,85m - ◆ 1,00m - ■ 1,00m  
⌚ 91W - ☈ 38,0kg

**GX098L**  
◆ 2,30m - ◆ 1,50m - ■ 0,90m  
⌚ 38W - ☈ 58,0kg

*H: 2m*  
**GX087L**  
◆ 2,00m - ◆ 2,00m - ■ 1,45m  
⌚ 75W - ☈ 87,0kg

*H: 4m*  
**GX086L-A**  
◆ 4,00m - ◆ 2,70m - ■ 2,50m  
⌚ 226W - ☈ 259,0kg  
with presence detector

*H: 4m*  
**GX086L**  
◆ 4,00m - ◆ 2,70m - ■ 2,50m  
⌚ 226W - ☈ 259,0kg

**GX039L**  
◆ 2,20m - ◆ 2,40m - ■ 0,70m  
⌚ 95W - ☈ 56,0kg

**GX212LW-S**  
◆ 1,50m - ◆ 1,50m - ■ 1,50m  
⌚ 24W - ☈ 37,0kg



3D Characters  
& animals



**GX139LW-S**  
◆ 1.90m - ♦ 2.66m - ■ 1.20m  
⌚ 77W - ⚡ 58.0kg

**GX137LW-S**  
◆ 3.00m - ♦ 3.09m - ■ 0.90m  
⌚ 68W - ⚡ 60.0kg

**GX140LW-S**  
◆ 2.40m - ♦ 3.60m - ■ 1.50m  
⌚ 24W - ⚡ 31.0kg

**GX135LW-S**  
◆ 1.50m - ♦ 1.16m - ■ 1.00m  
⌚ 29W - ⚡ 25.0kg



**GX136LW-S**  
◆ 4.00m - ♦ 4.60m - ■ 3.66m  
⌚ 116W - ⚡ 97.0kg

**GX138LW-S**  
◆ 4.00m - ♦ 3.00m - ■ 2.00m  
⌚ 96W - ⚡ 88.0kg

**GX141LW-S**  
◆ 1.90m - ♦ 1.80m - ■ 0.65m  
⌚ 40W - ⚡ 29.0kg


**GX142LW-S**  
◆ 2.30m - ♦ 2.10m - ■ 0.76m  
⌚ 58W - ⚡ 38.0kg




## Arches & trees

---

Although our audience is hugely diverse, young and old alike are looking for unforgettable experiences and walkthrough our elegant arches, bright trees and our fountains, streets and alleyways are given a welcoming and natural feel.



Detailed technical information p140 to 144



Detailed technical information p140 to 144




● SLEDO10W  
◆ 7.50m - ◆ 3.40m - ■ 3.40m  
↳ 265W - □ 152.0kg



● GX060L-W  
◆ 5.00m - ◆ 2.40m - ■ 2.40m  
↳ 360W - □ 199.0kg  
GX060L

Detailed technical information p140 to 144



Detailed technical information p140 to 144



2.10m  
● SL033W - ● SL033  
◆ 2.10m - ◆ 2.50m  
⚡ 45W - ⚡ 8.8kg  
1.50m :  
● SL032W - ● SL032

2.00m  
● SL013W - ● SL013  
◆ 2.00m - ◆ 3.50m  
⚡ 45W - ⚡ 9.0kg  
1.50m :  
● SL012W - ● SL012

● SL037W-S  
◆ 2.90m - ◆ 1.00m - ■ 1.00m  
⚡ 45W - ⚡ 51.0kg

● GX327LW  
◆ 1.10m - ◆ 1.00m - ■ 1.00m  
⚡ 25W - ⚡ 7.2kg  
● GX327L

● SL036W-S  
◆ 2.90m - ◆ 1.00m - ■ 1.00m  
⚡ 21W - ⚡ 31.0kg

**Presence sensors:**


an animated lighting display is triggered when the public approaches.

**Optional benches:** available for all the arches on these pages.

● SL034W-S  
 ♦ 3,00m - ♦ 4,30m  
 ♯ 241W - ☐ 137,0kg



Detailed technical information p140 to 144



96



By considering practical use in their innovative designs, our R&D department has devised the all-new LED+ in both static and slowflash editions to make your projects come alive! Our new and exclusive LED range is the outcome of a long-term collaboration with Nichia®, the world leader in LEDs. The range is:

+ bright, + robust, + long span, + consistent in terms of color


The new technical features of LED+:

- **Design is optimized and registered**  
to promote the luminous efficiency of our product (inverted cone principle).
- **Thermal dissipation is maximized**  
for longer LED life
- **Uniform phosphorus deposition**  
for a uniform lighting effect.
- **2 years guarantee**
- **Optimum protection index: IP66 / IP69**
- **Octoplus 230V Connection System by Blachere IP67**

# Garlands


---

## Blachere LEDs




Our standard LED model!

Bright and stable (lifespan and colour), our Classic LEDs also inverted cones (homogeneous light diffusion).



Garlands


97



## Sparklight® Led+ garlands with slowflash



requires 230V power supply cable L: 1,50m FY08+ type...  
and bridge rectifier FY043+ type... see page 136 to 139



| ◆       | LED                     | SLOWFLASH | P (W)                      | ●    | □         | ■        |
|---------|-------------------------|-----------|----------------------------|------|-----------|----------|
| 20,00 m | 108 ○                   | 52 ○      | 11,5                       | 100m | FL590BF+  | FL590F+  |
| 20,00 m | 108 ○                   | 52 ○      | 11,5                       | 100m | FL590WBF+ | FL590WF+ |
| 20,00 m | 108 ○                   | 52 ○      | 11,5                       | 100m | FL590BLF+ |          |
| 20,00 m | 108 ○                   | 52 ○      | 11,5                       | 100m |           | FL590RF+ |
| 1,50m   | 230V power supply cable |           | 690W max - see p136 to 139 |      | FY08-B+   | FY08+    |
| 0,30m   | bridge rectifier        |           | 690W max - see p136 to 139 |      | FY043A-B+ | FY043A+  |
| 0,20m   | bridge rectifier        |           | 230W max - see p136 to 139 |      | FY041A-B+ | FY041A+  |

### product info

#### Blachère exclusive

- Protected model
- High brightness
- Shock resistant IK06
- Long lifespan
- Even hue
- IP 66/69 protection rating. Maximum rating allowed for a 230V product.
- Flexible connectivity thanks to the extensive Octoplus 230V by Blachère range (see p.136 to 139)

### 2 YEARS GUARANTEE

conditions : contact us




100

101

## Sparklight® Led+ garlands static



requires 230V power supply cable L: 1,50m FY08+ type...  
and bridge rectifier FY043+ type... see page 136 to 139



| ◆       | LED                     | P (W)                      | ●    | □         | ■       |
|---------|-------------------------|----------------------------|------|-----------|---------|
| 20,00 m | 160 ○                   | 11,5                       | 100m | FL590-B+  | FL590+  |
| 20,00 m | 160 ○                   | 11,5                       | 100m | FL590W-B+ | FL590W+ |
| 20,00 m | 160 ○                   | 11,5                       | 100m | FL590BL+  |         |
| 20,00 m | 160 ○                   | 11,5                       | 100m |           | FL590R+ |
| 1,50m   | 230V power supply cable | 690W max - see p136 to 139 |      | FY08-B+   | FY08+   |
| 0,30m   | bridge rectifier        | 690W max - see p136 to 139 |      | FY043A-B+ | FY043A+ |
| 0,20m   | bridge rectifier        | 230W max - see p136 to 139 |      | FY041A-B+ | FY041A+ |

### product info

#### Blachère exclusive

- Protected model
- High brightness
- Shock resistant IK06
- Long lifespan
- Even hue
- IP 66/69 protection rating.
- Maximum rating allowed for a 230V product.
- Flexible connectivity thanks to the extensive Octoplus 230V by Blachère range (see p.136 to 139)

**2 YEARS GUARANTEE**

conditions : contact us




103

## Joylight® Led+ curtains with slowflash



requires 230V power supply cable L: 1,50m FY08+ type...  
and bridge rectifier FY043+ type... see page 136 to 139



| ◆       | ◆      | LED                     | SLOWFLASH | P (W)                      | ■  | □         | ■       |
|---------|--------|-------------------------|-----------|----------------------------|----|-----------|---------|
| 1,50 m  | 2,00 m | 150 ○                   | 60 ○      | 17                         | 15 | 27        | FL74BF+ |
| 1,50 m  | 2,00 m | 150 ●                   | 60 ●      | 17                         | 15 | 27        | FL74WF+ |
| 3,00 m  | 2,00 m | 240 ○                   | 120 ○     | 25                         | 15 | 18        | FL70BF+ |
| 3,00 m  | 2,00 m | 240 ●                   | 120 ●     | 25                         | 15 | 18        | FL70WF+ |
| 5,00 m  | 2,00 m | 360 ○                   | 180 ○     | 65                         | 15 | 9         | FL75BF+ |
| 5,00 m  | 2,00 m | 360 ●                   | 180 ●     | 65                         | 15 | 9         | FL75WF+ |
| 7,00 m  | 2,00 m | 510 ○                   | 240 ○     | 70                         | 15 | 9         | FL72BF+ |
| 7,00 m  | 2,00 m | 510 ●                   | 240 ●     | 70                         | 15 | 9         | FL72WF+ |
| 10,00 m | 2,00 m | 690 ○                   | 360 ○     | 80                         | 15 | 8         | FL79BF+ |
| 10,00 m | 2,00 m | 690 ●                   | 360 ●     | 80                         | 15 | 8         | FL79WF+ |
| 1,50m   |        | 230V power supply cable |           | 690W max - see p136 to 139 |    | FY08-B+   | FY08+   |
| 0,30m   |        | bridge rectifier        |           | 690W max - see p136 to 139 |    | FY043A-B+ | FY043A+ |
| 0,20m   |        |                         |           | 230W max - see p136 to 139 |    | FY041A-B+ | FY041A+ |


### product info

#### Blachère exclusive

- Protected model
- High brightness
- Shock resistant IK06
- Long lifespan
- Even hue
- IP 66/69 protection rating.
- Maximum rating allowed for a 230V product.
- Flexible connectivity thanks to the extensive Octoplus 230V by Blachère range (see p.136 to 139)

### 2 YEARS GUARANTEE

conditions - contact us




104

105

## Joylight® Led+ curtains static



requires 230V power supply cable L: 1,50m FY08+ type...  
and bridge rectifier FY043+ type... see page 136 to 139



| ◆       | ◆      | LED                     | P (W)                      | ■  | ■  | □         | ■       |
|---------|--------|-------------------------|----------------------------|----|----|-----------|---------|
| 1,50 m  | 2,00 m | 210 ○                   | 20                         | 15 | 25 | FL74-B+   | FL74+   |
| 1,50 m  | 2,00 m | 210 ○                   | 20                         | 15 | 25 | FL74W-B+  | FL74W+  |
| 3,00 m  | 2,00 m | 360 ○                   | 30                         | 15 | 16 | FL70-B+   | FL70+   |
| 3,00 m  | 2,00 m | 360 ○                   | 30                         | 15 | 16 | FL70W-B+  | FL70W+  |
| 5,00 m  | 2,00 m | 540 ○                   | 67                         | 15 | 9  | FL75-B+   | FL75+   |
| 5,00 m  | 2,00 m | 540 ○                   | 67                         | 15 | 9  | FL75W-B+  | FL75W+  |
| 7,00 m  | 2,00 m | 750 ○                   | 69                         | 15 | 9  | FL72-B+   | FL72+   |
| 10,00 m | 2,00 m | 1050 ○                  | 77                         | 15 | 9  | FL79-B+   | FL79+   |
| 10,00 m | 2,00 m | 1050 ○                  | 77                         | 15 | 9  | FL79-B+   | FL79W+  |
| 10,00 m | 2,00 m | 1050 ○                  | 77                         | 15 | 9  | FL79W-B+  | FL79W+  |
| 1,50m   |        | 230V power supply cable | 690W max - see p136 to 139 |    |    | FY08-B+   | FY08+   |
| 0,30m   |        | bridge rectifier        | 690W max - see p136 to 139 |    |    | FY043A-B+ | FY043A+ |
| 0,20m   |        | bridge rectifier        | 230W max - see p136 to 139 |    |    | FY041A-B+ | FY041A+ |

### product info

#### Blachère exclusive

- Protected model
- High brightness
- Shock resistant IK06
- Long lifespan
- Even hue
- IP 66/69 protection rating.
- Maximum rating allowed for a 230V product.
- Flexible connectivity thanks to the extensive Octoplus 230V by Blachère range (see p.136 to 139)

### 2 YEARS GUARANTEE

conditions - contact us




106

107

## Stalactitlight® Led+ with slowflash or static



requires 230V power supply cable L: 1,50m FY08+ type...  
and bridge rectifier FY043+ type... see page 136 to 139



### ► with slowflash

| ◆      | ◆                       | LED   | SLOWFLASH | P (W)                      | ■  | □  | □         |
|--------|-------------------------|-------|-----------|----------------------------|----|----|-----------|
| 0,80 m | 4,50 m                  | 120 ⓒ | 60 ⓒ      | 16                         | 48 | 20 | FL390BF+  |
| 0,80 m | 4,50 m                  | 120 ⓐ | 60 ⓐ      | 16                         | 48 | 20 | FL390WB+  |
| 1,50m  | 230V power supply cable |       |           | 690W max - see p136 to 139 |    |    | FY08-B+   |
| 0,30m  | bridge rectifier        |       |           | 690W max - see p136 to 139 |    |    | FY043A-B+ |

### ► static

| ◆      | ◆                       | LED   | P (W)                      | ■  | □  | □         |
|--------|-------------------------|-------|----------------------------|----|----|-----------|
| 0,80 m | 4,50 m                  | 120 ⓒ | 16                         | 48 | 20 | FL390B+   |
| 0,80 m | 4,50 m                  | 120 ⓐ | 16                         | 48 | 20 | FL390WB+  |
| 1,50m  | 230V power supply cable |       | 690W max - see p136 to 139 |    |    | FY08-B+   |
| 0,30m  | bridge rectifier        |       | 690W max - see p136 to 139 |    |    | FY043A-B+ |

### product info

#### Blachère exclusive


- Protected model
- High brightness
- Shock resistant IK06
- Long lifespan
- Even hue
- IP 66/69 protection rating. Maximum rating allowed for a 230V product.
- Flexible connectivity thanks to the extensive Octoplus 230V by Blachère range (see p.136 to 139)

### 2 YEARS GUARANTEE

conditions - contact us



## Sparklight® garlands with flash or static



### ► with flash

| ◆       | LED   | FLASH | P (W) |      |  |  | ■        |
|---------|-------|-------|-------|------|--|--|----------|
| 20,00 m | 90 ○  | 30 ○  | 8     | 100m |  |  | 512-FX   |
| 20,00 m | 90 ○  | 30 ○  | 8     | 100m |  |  | 512W-FX  |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 511-FX   |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 510BW-FX |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 510W-FX  |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 510B-FX  |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 510R-FX  |
| 20,00 m | 150 ○ | 50 ○  | 15,5  | 100m |  |  | 510P-FX  |

### ► 100% flash

| ◆       | LED  | P (W) |      |  |  | ■      |
|---------|------|-------|------|--|--|--------|
| 20,00 m | 80 ○ | 5     | 100m |  |  | 510-FX |

### ► static

| ◆       | LED   | P (W) |      |  |        | ■     |
|---------|-------|-------|------|--|--------|-------|
| 20,00 m | 200 ○ | 15    | 100m |  | 508-B  | 508   |
| 20,00 m | 200 ○ | 15    | 100m |  | 508W-B | 508W  |
| 20,00 m | 200 ○ | 15    | 100m |  |        | 508B  |
| 20,00 m | 120 ○ | 8     | 100m |  |        | 512C  |
| 20,00 m | 120 ○ | 8     | 100m |  |        | 512CW |

### product info

- Past reliability
- Power supply with connecting socket included
- Wide range of Octoplus 230V by Blachère accessories available (see p.136 to 139)
- High flash concentration on FX models
- Increased waterproofing thanks to optimum protection rating.



## Joylight® curtains with flash or static




### ► with flash

| ◆       | ◆      | LED    | FLASH | P (W) | ■  | ■  | □       |
|---------|--------|--------|-------|-------|----|----|---------|
| 0,80 m  | 2,00 m | 140 ○  | 28 ○  | 14    | 14 | 30 | 21CBFX  |
| 0,80 m  | 2,00 m | 140 ○  | 28 ○  | 14    | 14 | 30 | 21CWBFX |
| 1,50 m  | 2,00 m | 210 ○  | 30 ○  | 15    | 15 | 25 | 24CBFX  |
| 1,50 m  | 2,00 m | 210 ○  | 30 ○  | 15    | 15 | 25 | 24CWBFX |
| 1,50 m  | 2,00 m | 210 ●  | 30 ○  | 15    | 15 | 25 | 24CRFX  |
| 1,50 m  | 2,00 m | 210 ○  | 30 ○  | 15    | 15 | 25 | 24CBLFX |
| 3,00 m  | 2,00 m | 420 ○  | 56 ○  | 33    | 14 | 16 | 20CBFX  |
| 3,00 m  | 2,00 m | 420 ○  | 56 ○  | 33    | 14 | 16 | 20CWBFX |
| 3,00 m  | 2,00 m | 420 ●  | 56 ○  | 33    | 14 | 16 | 20CRFX  |
| 3,00 m  | 2,00 m | 420 ○  | 56 ○  | 33    | 14 | 16 | 20CBLFX |
| 5,00 m  | 2,00 m | 900 ○  | 90 ○  | 55    | 15 | 12 | 25CBFX  |
| 5,00 m  | 2,00 m | 900 ○  | 90 ○  | 55    | 15 | 12 | 25CWBFX |
| 5,00 m  | 2,00 m | 900 ●  | 90 ○  | 55    | 15 | 12 | 25CRFX  |
| 5,00 m  | 2,00 m | 900 ○  | 90 ○  | 55    | 15 | 12 | 25CBLFX |
| 7,00 m  | 2,00 m | 1200 ○ | 120 ○ | 55    | 15 | 12 | 22CBFX  |
| 7,00 m  | 2,00 m | 1200 ○ | 120 ○ | 80    | 15 | 8  | 22CWBFX |
| 10,00 m | 2,00 m | 1350 ○ | 135 ○ | 84    | 15 | 8  | 29CBFX  |
| 10,00 m | 2,00 m | 1350 ○ | 135 ○ | 84    | 15 | 8  | 29CWBFX |

### ► static

| ◆       | ◆      | LED    | P (W) | ■  | ■  | □      |
|---------|--------|--------|-------|----|----|--------|
| 1,50 m  | 2,00 m | 342 ○  | 30    | 18 | 20 | 24C-B  |
| 1,50 m  | 2,00 m | 342 ○  | 30    | 18 | 20 | 24CW-B |
| 3,00 m  | 2,00 m | 540 ○  | 35    | 18 | 15 | 20C-B  |
| 3,00 m  | 2,00 m | 540 ○  | 35    | 18 | 15 | 20CW-B |
| 5,00 m  | 2,00 m | 900 ○  | 65    | 18 | 9  | 25C-B  |
| 5,00 m  | 2,00 m | 900 ○  | 65    | 18 | 9  | 25CW-B |
| 7,00 m  | 2,00 m | 1080 ○ | 72    | 18 | 9  | 22C-B  |
| 7,00 m  | 2,00 m | 1080 ○ | 72    | 18 | 9  | 22CW-B |
| 10,00 m | 2,00 m | 1350 ○ | 58    | 18 | 10 | 29C-B  |
| 10,00 m | 2,00 m | 1350 ○ | 58    | 18 | 10 | 29CW-B |



### product info

Ideal for decorating facades  
Trees or for cross-street motifs.


Up to 30 curtains on the same  
power supply.

Compatible with the entire range

Connection options with the  
Octoplus 230V by Blachere®  
accessories p.136 to 139.



## Joylight® Slowglow curtains



| ◆       | ◆      | LED Slowglow | P (W) | ■  | ■  | □     |
|---------|--------|--------------|-------|----|----|-------|
| 1,50 m  | 2,00 m | 120 ○        | 16    | 15 | 13 | 24SG  |
| 1,50 m  | 2,00 m | 120 ●        | 16    | 15 | 13 | 24WSG |
| 3,00 m  | 2,00 m | 180 ○        | 15    | 15 | 12 | 20SG  |
| 3,00 m  | 2,00 m | 180 ●        | 15    | 15 | 12 | 20WSG |
| 5,00 m  | 2,00 m | 210 ○        | 17    | 15 | 12 | 25SG  |
| 5,00 m  | 2,00 m | 210 ●        | 17    | 15 | 12 | 25WSG |
| 7,00 m  | 2,00 m | 225 ○        | 17    | 15 | 12 | 22SG  |
| 7,00 m  | 2,00 m | 225 ●        | 17    | 15 | 12 | 22WSG |
| 10,00 m | 2,00 m | 270 ○        | 15    | 15 | 13 | 29SG  |
| 10,00 m | 2,00 m | 270 ●        | 15    | 15 | 13 | 29WSG |

### product info

New animation exclusive to Blachère illumination.


Gentle lighting effect, snowflake effect.

Compatible with the entire range.


Connection options with Octoplus® 230V by Blachère® accessories p.136 to 139.



## Stalactitlight® with flash or static



352-FX / 352W-FX / 352R-FX / 352B-FX / 354-FX  
354W-FX / 352 / 352W / 354 / 354W



353C / 353CW

### ► with flash

| ◆      | ◆      | LED   | FLASH | P (W) | m  | mm | □       |
|--------|--------|-------|-------|-------|----|----|---------|
| 0,57 m | 4,50 m | 156 ○ | 48 ○  | 13    | 48 | 15 | 352-FX  |
| 0,57 m | 4,50 m | 156 ○ | 48 ○  | 13    | 48 | 15 | 352W-FX |
| 0,57 m | 4,50 m | 156 ● | 48 ○  | 13    | 48 | 15 | 352R-FX |
| 0,57 m | 4,50 m | 156 ○ | 48 ○  | 13    | 48 | 15 | 352B-FX |
| 1,00 m | 4,50 m | 180 ○ | 60 ○  | 12    | 36 | 15 | 354-FX  |
| 1,00 m | 4,50 m | 180 ○ | 60 ○  | 12    | 36 | 15 | 354W-FX |

### ► static

| ◆      | ◆      | LED   | P (W) | m  | mm | □     |
|--------|--------|-------|-------|----|----|-------|
| 0,57 m | 4,50 m | 180 ○ | 12    | 48 | 15 | 352   |
| 0,57 m | 4,50 m | 180 ○ | 12    | 48 | 15 | 352W  |
| 1,00 m | 4,50 m | 240 ○ | 12    | 36 | 15 | 354   |
| 1,00 m | 4,50 m | 240 ○ | 12    | 36 | 15 | 354W  |
| 1,50 m | 4,50 m | 320 ○ | 16    | 32 | 15 | 353C  |
| 1,50 m | 4,50 m | 320 ○ | 16    | 32 | 15 | 353CW |

### product info

An absolute must since its creation, this product is a best-seller owing to its reliability.

Can be divided into 10m sections for greater adaptability.

Compatible with the entire range.

Connection possibilities with the Octoplus 230V by Blachere® accessories p.136 to 139.



## Hanging bouquets indoor & outdoor



### ► Indoor use / IP20

| Ø   | Colour | LED   | FLASH | P (W) |             |
|---|--------|-------|-------|-------|-------------|
| 0,80 m                                    | Silver | 441 ⚡ | 63 ⚡  | 25    | FCL080A     |
| 0,80 m                                    | Gold   | 441 ⚡ | 63 ⚡  | 25    | FCL080G     |
| Transformateur intérieur pour bouquet FCL |        |       |       |       | 25 PRTR24VI |

### product info

The hanging bouquets are flash animated with a gold or silver decoration, visible by day.

Works with a PRTR24VI or PRTR24V transformer - sold separately.

### ► Outdoor use / IP55



| Ø   | Colour | LED   | FLASH | P (W) |            |
|---|--------|-------|-------|-------|------------|
| 0,80 m                                    | Silver | 441 ⚡ | 63 ⚡  | 25    | FCL080A-E  |
| 0,80 m                                    | Gold   | 441 ⚡ | 63 ⚡  | 25    | FCL080G-E  |
| Transformateur extérieur pour bouquet FCL |        |       |       |       | 25 PRTR24V |



118

119

## Nostalgia stalactite and Garland



### ► stalactite

| ◆      | ◆      | LED  | ●  | P (W) | ■  | □  |        |
|--------|--------|------|----|-------|----|----|--------|
| 1,00 m | 4,50 m | 48 ● | 48 | 20    | 15 | 12 | FL361W |

### ► garland

| ◆    | LED   | FLASH | ●  | P (W) | ■  | □       |  |
|------|-------|-------|----|-------|----|---------|--|
| 10 m | 120 ● | 20 ○  | 35 | 10    | 15 | 570W-FX |  |


### info produit

Garlands and stalactite « ready to install ».

Delivered with ø3mm PVC-sheathed steel rope for crosswise attachment.



## Nostalgia XL suspended bulbs




### ► set of 4 bulbs

| ◆      | ◆      | ●              | microLED | FLASH | P (W) | ■       |
|--------|--------|----------------|----------|-------|-------|---------|
| 2,00 m | 2,00 m | ø28cm - H 50cm | 400 ●    | 200 ● | 8     | FL930BB |

### ► individual bulb

|   |       |      |   |           |
|---|-------|------|---|-----------|
| 1 bulb - connection on FYPRTR9 only (not supplied)              | 100 ● | 50 ● | 2 | G-FL930BB |
| 230V -> 24V transformer with Octoplus connector see p136 to 139 |       |      |   | FYPRTR9   |



### product info

Ideal for tree decorations or suspended on ropes, these oversized bulbs also twinkle.


A very trendy retro effect !

Available in packs of 4 bulbs that come with a transformer, or singles (transformer and Octoplus accessories p.136 to 139).

Aluminium lamp cap (stainless).



## Hanging balls with animations





### ► set of 5 spheres

| ◆      | ◆      | animation             | ◆           | P (W) | ■       |
|--------|--------|-----------------------|-------------|-------|---------|
| 3,00 m | 1,20 m | flickering effect     | 5 ● ø20cm   | 15    | FL920LU |
| 3,00 m | 1,20 m | snowflakes projection | 5 ● ø20cm   | 24    | FL920SF |
| 3,00 m | 1,20 m | random colour change  | 5 RGB ø20cm | 24    | FL920M  |

### ► individual sphere

|  |             |     |           |
|--|-------------|-----|-----------|
| 1 ball ø20cm - linking on FYPTR9 only (not supplied) | 1 ● ø20cm   | 3   | G-FL920LU |
| 1 ball ø20cm - linking on FYPTR9 only (not supplied) | 1 ● ø20cm   | 4,5 | G-FL920SF |
| 1 ball ø20cm - linking on FYPTR9 only (not supplied) | 1 RGB ø20cm | 4,5 | G-FL920M  |
| 230V -> 24V transformer with Octopus connector pi38  |             |     | FYPTR9    |



### product info

Ideal for tree decorations or suspended on ropes.


Simulate the warm light of candles with a new flickering animation.

A very trendy retro effect.

Set of 5 spheres or individual.



## Pre-lighted swag garland



### ► swag garland per unit

| ◆      | Ø      | LED | P (W) |   | ■      |
|--------|--------|-----|-------|---|--------|
| 3,00 m | 0,35 m | 400 | 30    | 6 | GP303W |
| 4,00 m | 0,35 m | 500 | 38    | 4 | GP304W |


### product info

Great classic of traditional street decorations.

Quick-fit accessories, extension leads, multi-socket connectors : see pt36 to 139



## Synthetic pre-lighted fir tree garlands (set of 2)



### ► with flash

| ◆      | Ø      | LED | FLASH | P (W) |    | █         |
|--------|--------|-----|-------|-------|----|-----------|
| 2,70 m | 0,30 m | 180 | 60    | 11    | 10 | GP134LWFX |

### ► static

| ◆      | Ø      | LED | P (W) |    | █        |
|--------|--------|-----|-------|----|----------|
| 2,70 m | 0,30 m | 240 | 11    | 10 | GP134L-W |


### product info

Great classic of traditional street decorations.

Quick-fit accessories, extension leads, multi-socket connectors : See p136 to 139.



## Braid garlands with flash or static



### ► with flash

| ◆      | Ø        | LED   | FLASH | P (W) |    |         |
|--------|----------|-------|-------|-------|----|---------|
| 7,50 m | 12,00 cm | 210 ⚒ | 30 ⚒  | 13    | 13 | TSL3FX  |
| 7,50 m | 12,00 cm | 210 ⚒ | 30 ⚒  | 13    | 13 | TSL3WFX |

### ► static

| ◆      | Ø       | LED   | P (W) |    |       |
|--------|---------|-------|-------|----|-------|
| 7,50 m | 6,00 cm | 240 ⚒ | 13    | 13 | TSL2  |
| 7,50 m | 6,00 cm | 240 ⚒ | 13    | 13 | TSL2W |

### product info


« Ready-to-fit ».

Strong lighting density.

Supplied on Ø 3mm sheathed steel wire rope.  
Quick-fit accessories.  
Multi-socket connectors.  
Animation kit : p136 to 139



## Nicia® garlands with flash



### product info

« Ready-to-fit ».

Strong lighting density.

Quick-fit accessories.  
Multi-socket connectors,  
Animation kit : pt36 to 139

| ◆      | Ø       | LED   | FLASH | P (W) |   | □       |
|--------|---------|-------|-------|-------|---|---------|
| 6,00 m | 6,00 cm | 432 ⚡ | 48 ⚡  | 23    | 9 | 558-FX  |
| 6,00 m | 6,00 cm | 432 ☺ | 48 ⚡  | 23    | 9 | 558W-FX |

## Octoplus by Blachère®

Exclusivity



Octoplus by Blachère® 230V connector, protection rating IP67, according the European standard EN60529 on the degree of protection provided by enclosures.



Safety extra-low voltage connector 12/24V


**Octoplus** is the connector that enables **fast and multiple connection** between our decorations and most of our range of garlands. Each item that is marked "Octoplus" can therefore **be connected** to another "Octoplus" item. This means **the combination of items is infinite** just by simplifying the electrical connections.

## Octoplus®: Example of use N°1



| For a transverse motif |          |
|------------------------|----------|
| Ref.                   | Quantity |
| FY08-B+                | 1        |
| FY043A-B+              | 1        |
| FY01-3B+               | 1        |
| FL390WBF+              | 1        |
| FYT-B+                 | 2        |
| ITL021                 | 2        |

To install on steel wire with PVC sheath




## Octoplus®: Example of use No2




For a width of 4.50m

| Ref.      | Quantity |
|-----------|----------|
| FY08-B+   | 1        |
| FY043A-B+ | 1        |
| FY01-2B+  | 1        |
| 354CW     | 1        |
| FYT-B+    | 2        |
| FYPRTR9   | 2        |
| G-FL900   | 2        |

To install on steel wire  
with PVC sheath



## Octoplus®: Example of use No3



| Ref.      | Quantity |
|-----------|----------|
| FY08-B+   | 1        |
| FY043A-B+ | 1        |
| FY01-3+   | 2        |
| BTX8      | 1        |
| 508W      | 10       |
| FY030+    | 4        |
| FYPRTR9   | 1        |
| G-FL900   | 1        |
| FY03B22   | 1        |
| FXL08-B22 | 1        |
| F722-L    | 1        |





## 230V Connections

| Diagram/Picture | Description  | Obs.                           | <input checked="" type="checkbox"/>  | <input type="checkbox"/>  |
|-----------------|--|--------------------------------|--|---|
|                 | Power cable<br>230V - 1.5m - HO5RN-F - 2x1mm <sup>2</sup><br>with male plug and female Octoplus connector  | Euro<br>UK<br>Swiss<br>Wieland | FY08+<br>FY08-UK+<br>FY08-S+<br>FY08-W                                     | FY08-B+<br>FY08-BUK+<br>FY08-BS+<br>FY08-BW   |
|                 | AC/DC bridge rectifier (compulsory) for LED+ with Octoplus connector (M+F)   |                                | FY041A+<br>FY043A+<br>FY01-1+<br>FY01-2+<br>FY01-3+<br>FY01-5+<br>FY01-10+ | FY041A-B+<br>FY043A-B+<br>FY01-1B+<br>FY01-2B+<br>FY01-3B+<br>FY01-5B+<br>FY01-10B+ |
|                 | Octoplus extension<br>230V - HO5RN-F - 2x1mm <sup>2</sup>  |                                | FY1C+  | FY1CB+  |
|                 | Set of 5 end-caps plugs  |                                |  |   |
|                 | T connector 230V   |                                | FYT+   | FYT-B+  |
|                 | Y connector 230V   |                                | FY030+   | FY030-B+  |
|                 | W connector 230V   |                                | FY031+   | FY031-B+  |
|                 | Collector - 230V - HO5RN-F<br>L = 2 x 1.60m = 3.20m<br>20cm between connectors with 16 sockets and steel wire with PVC-coating<br>690 W max in total |                                | FY023+   | FY023-B+  |



## 230V Connections

| Diagram/Picture | Description  | Obs.      | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|-----------------|--|-----------|-------------------------------------|--------------------------|
|                 | IP66 multi-socket box with 4 Octoplus (F) outputs and one Octoplus (M) input       | 690 W max | BTX4                                | BTX4-B                   |
|                 | IP66 multi-socket box with 8 Octoplus (F) outputs and one Octoplus (M) input       | 690 W max | BTX8                                | BTX8-B                   |
|                 | 230V adaptor Sparklight and Stalactites (connector 2017 -> connector 2018)         | -         | FY230F2                             | FY230F2-B                |
|                 | 230V adaptor Sparklight and Stalactites (connector 2018 -> connector 2017)         | -         | FY230M1                             | FY230M1-B                |
|                 | B22 bushing with M/F Octoplus connector  | 5W max    | FY03B22                             | FY03B22-B                |
|                 | Elasticated "SPECIAL TREE" connector to let the tree grow without any restrictions | set of 5  | FY07A                               | -                        |
|                 | Wieland female socket (install at top of candelabra) + 6m of HO5RN-F power cable   | -         | FY06-P                              | -                        |
|                 | 20cl tube of silicone sealant for full sealing of connectors (extreme environment) | -         | NLC60                               | -                        |
|                 | IP66 quick connector for HO5RN-F cable   | -         | BT04                                | -                        |
|                 | Protective and adhesive foam   | set of 10 | FY-MOUS                             | -                        |



## 24V Connections

| Diagram/Picture | Description   | Obs.    | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|-----------------|---|---------|-------------------------------------|--------------------------|
|                 | 1m extension PVC cord<br>24V<br>Connectors M-C1/F-C2  |         | FY01-PVC                            | FY01B-PVC                |
|                 | 2m extension PVC cord<br>24V<br>Connectors M-C1/F-C2  |         | FY02-PVC                            | FY02B-PVC                |
|                 | 5m extension PVC cord<br>24V<br>Connectors M-C1/F-C2  |         | FY05-PVC                            | FY05B-PVC                |
|                 | 2 output connector PVC<br>24V<br>Connectors M-C1/F-C2 |         | FY2-PVC                             | FY2B-PVC                 |
|                 | 3 output connector PVC<br>24V<br>Connectors M-C1/F-C2 |         | FY3-PVC                             | FY3B-PVC                 |
|                 | 230V -> 24V transformer<br>with Octoplus connector    | 10W max | FYPRTR9                             | FYPRTR9B                 |

## Fixing accessories for motifs




In inverted cone  
1PIX03 (up)  
1PIX04 (down)  
2 curtains H : 5m

In cylinder  
2 PIX03  
1 PIX02 (down)  
2 curtains H : 5m

In Christmas tree  
1 PIX04 (up)  
1 PIX02 (down)  
1 curtain H : 3m

Free composition  
2 PIX03  
1 FL74WBF+  
1 FL900E



**Circular brackets**  
Put together low-price 3D decorations  
on your columns with our circular brackets  
(inner diameter adjustable)

| Ref.  | $\varnothing$ | Perimeter | pole $\varnothing$ | usable with                            |
|-------|---------------|-----------|--------------------|--|
| PIX04 | 25 cm         | 0,80 m    | 60 à 120 mm        | Curtains<br>p103, 105, 111,<br>and 113 |
| PIX02 | 60 cm         | 1,90 m    | 60 à 200 mm        |  |
| PIX03 | 130 cm        | 4,00 m    | 60 à 200 mm        |  |

| Code      | Page | Height | Width | Length | Diameter | Power (W) | Weight | Led colour              | Animation             | Flash color | Bioprint colour | No of elements | Mounting   |
|-----------|------|--------|-------|--------|----------|-----------|--------|-------------------------|-----------------------|-------------|-----------------|----------------|------------|
| CIME2     | 43   | 1      |       |        |          | 30        | 9.6    | pure white / warm white | flash                 | pure white  |                 | 1              | treetop    |
| CIME4     | 43   | 1      |       |        |          | 55        | 11.2   | pure white              |                       | white       |                 | 2              | treetop    |
| CIME6     | 43   | 1      |       |        |          | 46        | 13     | pure white / warm white | slowflash             | warm white  | gold            | 1              | treetop    |
| CIME7     | 43   | 0.8    |       |        |          | 16        | 10     | pure white              |                       | white       |                 | 2              | treetop    |
| FCL080A-E | 49   | 0.8    |       |        | 0.8      | 15        | 3.62   | pure white              | flash                 | pure white  |                 | 1              | suspension |
| FCL080G-E | 49   | 0.8    |       |        | 0.8      | 15        | 3.62   | warm white              | flash                 | pure white  |                 | 1              | suspension |
| FML180    | 57   | 1.5    |       |        |          | 0.2       |        | pure white              | flash                 | pure white  |                 | 1              |            |
| FML180W   | 57   | 1.5    |       |        |          | 0.2       |        | warm white              | flash                 | pure white  |                 | 1              |            |
| GP157W    | 57   | 2.1    |       |        | 1.35     | 40        | 18     | warm white              |                       |             |                 | 1              | ground     |
| GSV140    | 57   | 1.4    |       |        | 0.6      |           |        |                         |                       |             |                 | 2              | ground     |
| GSV140B   | 57   | 1.4    |       |        | 0.6      |           |        |                         |                       |             |                 | 2              | ground     |
| GX001-L   | 90   | 5      |       |        | 5        | 315       | 206    | pure white              |                       |             |                 | 51             | ground     |
| GX001-LW  | 90   | 5      |       |        | 5        | 315       | 206    | warm white              |                       |             |                 | 51             | ground     |
| GX039L    | 79   | 2.2    | 2.4   | 0.7    |          | 95        | 56     | multicoloured           | flash / slowglow      | pure white  |                 | 1              | ground     |
| GX042L    | 77   | 2.2    | 1.2   | 0.8    |          | 18        | 39     | pure white / warm white | flash                 | pure white  | gold            | 1              | ground     |
| GX048LW   | 49   | 0.73   | 0.48  | 0.48   |          | 40        | 4.3    | warm white              | anim                  |             |                 | 1              | transverse |
| GX057LW   | 55   | 2.5    |       |        | 1.6      | 40        | 53     | warm white              |                       |             |                 | 1              | ground     |
| GX058LW   | 55   | 2.1    | 0.24  | 0.48   |          | 15        | 31     | warm white              |                       |             |                 | 1              | ground     |
| GX059LW   | 55   | 3      | 0.4   | 0.8    |          | 24        | 32     | warm white              |                       |             |                 | 1              | ground     |
| GX060L    | 89   | 5      |       |        | 2.4      | 360       | 199    | pure white              |                       |             |                 | 17             | ground     |
| GX060L-W  | 89   | 5      |       |        | 2.4      | 360       | 199    | warm white              |                       |             |                 | 17             | ground     |
| GX070LR-S | 84   | 3.9    | 3.6   | 3.3    |          | 260       | 235    | warm white / red        |                       | gold / red  |                 | 11             | ground     |
| GX075LW-S | 65   | 5      | 1.2   | 1.2    |          | 170       | 32     | warm white              |                       |             |                 | 1              | transverse |
| GX076LW-S | 65   | 5      |       |        | 2.4      | 480       | 57     | warm white              |                       |             |                 | 2              | transverse |
| GX081LW-2 | 40   | 5      |       |        | 3.56     | 245       | 263    | warm white              | slowglow              |             |                 | 46             | ground     |
| GX082LW   | 40   | 8      |       |        | 4.7      | 770       | 1112   | warm white              | slowglow              |             |                 | 107            | ground     |
| GX083LW   | 40   | 12     |       |        | 5.9      | 1870      | 2750   | warm white              | slowglow              |             |                 | 194            | ground     |
| GX086L    | 79   | 4      | 2.7   | 2.5    |          | 226       | 259    | multicoloured           | flash                 | pure white  |                 | 4              | ground     |
| GX086L-A  | 79   | 4      | 2.7   | 2.5    |          | 226       | 259    | multicoloured           | interactivity / flash | pure white  |                 | 4              | ground     |
| GX087L    | 79   | 2      | 2     | 1.45   |          | 75        | 87     | multicoloured           | flash                 | pure white  |                 | 1              | ground     |
| GX092L    | 76   | 2.2    | 1.15  | 0.7    |          | 22        | 30     | warm white / red        | flash                 | pure white  |                 | 1              | ground     |
| GX093L    | 76   | 2      | 1.2   | 0.6    |          | 22        | 22     | warm white / red        | flash                 | pure white  |                 | 1              | ground     |
| GX097L    | 78   | 2      | 1.3   | 0.6    |          | 24        | 31     | multicoloured           |                       | gold        |                 | 1              | ground     |
| GX098L    | 78   | 2.3    | 1.5   | 0.9    |          | 38        | 58     | multicoloured           |                       | gold        |                 | 1              | ground     |

| Code      | Page | Height | Width | Length | Diameter | Power (W) | Weight | Led colour              | Animation            | Flash color | Bioprint colour | No of elements      | Mounting |            |
|-----------|------|--------|-------|--------|----------|-----------|--------|-------------------------|----------------------|-------------|-----------------|---------------------|----------|------------|
| GX104L-S  | 77   | 2.15   | 0.85  | 0.96   |          | 62        | 30     | pure white / warm white |                      |             |                 | white / gold        | 3        | ground     |
| GX116LW   | 49   | 0.7    |       | 0.6    |          | 15        | 2.8    | warm white              | anim                 |             |                 |                     | 1        | suspension |
| GX117LW   | 48   | 2      |       |        | 1.5      | 126       | 33     | warm white              | slowflash            | warm white  | gold            |                     | 1        | suspension |
| GX130L    | 78   | 1.85   | 1     | 1      |          | 91        | 38     | warm white              |                      |             |                 |                     | 1        | ground     |
| GX132L    | 77   | 3.6    | 2.6   | 1.9    |          | 101       | 96     | pure white / red        | flash                | pure white  | gold            | 3                   | ground   |            |
| GX135LW-S | 80   | 1.5    | 1     | 1.16   |          | 29        | 25     | warm white              |                      |             |                 | Tubbing transparent | 1        | ground     |
| GX136LW-S | 81   | 4      | 3.66  | 4.6    |          | 116       | 97     | warmwhite               |                      |             |                 | Tubbing transparent | 3        | ground     |
| GX137LW-S | 80   | 3      | 0.9   | 3.09   |          | 68        | 60     | warmwhite               |                      |             |                 | Tubbing transparent | 2        | ground     |
| GX138LW-S | 81   | 4      | 2     | 3      |          | 96        | 88     | warmwhite               |                      |             |                 | Tubbing transparent | 3        | ground     |
| GX139LW-S | 80   | 1.9    | 1.2   | 2.66   |          | 77        | 58     | warmwhite               |                      |             |                 | Tubbing transparent | 1        | ground     |
| GX140LW-S | 80   | 2.4    | 1.5   | 3.6    |          | 87        | 70     | warmwhite               |                      |             |                 | Tubbing transparent | 2        | ground     |
| GX141LW-S | 81   | 1.9    | 0.65  | 1.8    |          | 40        | 29     | warmwhite               |                      |             |                 | Tubbing transparent | 1        | ground     |
| GX142LW-S | 81   | 2.3    | 0.76  | 2.1    |          | 58        | 38     | warmwhite               |                      |             |                 | Tubbing transparent | 1        | ground     |
| GX194L    | 76   | 1.2    | 2.3   | 1.2    |          | 79        | 82     | warm white              | xled / stars / flash | pure white  | gold            | 1                   | ground   |            |
| GX212LW-S | 79   | 1.5    | 1.5   | 1.5    |          | 24        | 37     | warm white              |                      |             |                 |                     | 1        | ground     |
| GX213LW-S | 86   | 5      |       |        | 5        | 240       | 457    | warm white              |                      |             |                 |                     | 29       | ground     |
| GX300LW-S | 91   | 4      |       |        | 4        | 150       | 84     | warm white              |                      |             |                 |                     | 27       | ground     |
| GX327L    | 93   | 1.1    |       |        | 1        | 25        | 7.2    | pure white              | flash                | pure white  |                 |                     | 1        | ground     |
| GX327LW   | 93   | 1.1    |       |        | 1        | 25        | 7.2    | warm white              | flash                | pure white  |                 |                     | 1        | ground     |
| IPL039W-S | 68   | 2      |       | 0.72   |          | 35        | 6.2    | pure white / warm white |                      |             |                 | white               | 1        | pole       |
| IPL113W   | 47   | 2      |       | 0.9    |          | 55        | 7.8    | warm white              | slowflash            | warm white  | gold            | 1                   | pole     |            |
| IPL114W   | 47   | 2      |       | 0.9    |          | 65        | 9.3    | warm white              | slowflash            | warm white  | gold            | 1                   | pole     |            |
| IPL139W   | 44   | 3      |       | 1.2    |          | 33        | 15     | warm white              | slowflash            |             | gold            | 1                   | pole     |            |
| IPL140W   | 44   | 1.6    |       | 0.65   |          | 33        | 15     | warm white              | slowflash            | warm white  | gold            | 1                   | pole     |            |
| ITGL102   | 72   | 0.6    | 0.4   | 0.24   |          | 16        | 4      | pure white              |                      |             |                 |                     | 2        | suspension |
| ITGL102W  | 72   | 0.6    | 0.4   | 0.24   |          | 16        | 4      | warm white              |                      |             |                 |                     | 2        | suspension |
| ITGL104   | 73   | 0.5    | 0.5   | 0.26   |          | 22        | 4      | pure white              |                      |             |                 |                     | 2        | suspension |
| ITGL104W  | 73   | 0.5    | 0.5   | 0.26   |          | 22        | 4      | warm white              |                      |             |                 |                     | 2        | suspension |
| ITGL105   | 73   | 0.8    | 0.8   | 0.4    |          | 44        | 8      | pure white              |                      |             |                 |                     | 2        | suspension |
| ITGL105W  | 73   | 0.8    | 0.8   | 0.4    |          | 44        | 8      | warm white              |                      |             |                 |                     | 2        | suspension |

| Code      | Page | Height | Width | Length | Diameter | Power (W) | Weight | Led colour              | Animation     | Flash color | Bioprint colour | No of elements | Mounting   |
|-----------|------|--------|-------|--------|----------|-----------|--------|-------------------------|---------------|-------------|-----------------|----------------|------------|
| ITGL107   | 73   | 0.5    | 0.5   | 0.26   |          | 22        | 4      | pure white              |               |             |                 | 2              | suspension |
| ITGL108   | 73   | 0.8    | 0.8   | 0.4    |          | 44        | 8      | pure white              |               |             |                 | 2              | suspension |
| ITGL109   | 72   | 0.5    | 0.5   | 0.12   |          | 8         | 2      | pure white              |               |             |                 | 2              | suspension |
| ITGL109W  | 72   | 0.5    | 0.5   | 0.12   |          | 8         | 2      | warm white              |               |             |                 | 2              | suspension |
| ITGL111   | 72   | 0.8    | 0.8   | 0.18   |          | 16        | 4      | pure white              |               |             |                 | 2              | suspension |
| ITGL117R  | 73   | 0.6    | 0.6   | 0.46   |          | 8         | 2      | red                     |               |             |                 | 2              | suspension |
| ITL016    | 62   | 3.1    | 3.1   |        |          | 200       | 25     | pure white              | flash         | pure white  | white           | 2              | suspension |
| ITL016W   | 62   | 3.1    | 3.1   |        |          | 200       | 25     | pure white / warm white | flash         | pure white  | white           | 2              | suspension |
| ITL017    | 63   | 2.02   | 2.02  |        |          | 135       | 16     | pure white              | stars / flash | pure white  | white           | 1              | suspension |
| ITL019    | 63   | 2      | 2     |        |          | 95        | 13.2   | pure white / warm white | flash         | pure white  | white           | 1              | suspension |
| ITL020B   | 63   | 0.97   | 0.85  |        |          | 40        | 4.2    | pure white / blue       | flash         | pure white  | white           | 1              | suspension |
| ITL020W   | 63   | 0.97   | 0.85  |        |          | 40        | 4.2    | pure white / warm white | flash         | pure white  | white           | 1              | suspension |
| ITL021    | 63   | 1.25   | 1.25  |        |          | 55        | 5.2    | pure white              |               | white       |                 | 1              | suspension |
| ITL022    | 63   | 0.97   | 0.85  |        |          | 30        | 3.2    | pure white              |               | white       |                 | 1              | suspension |
| ITL022W   | 63   | 0.97   | 0.85  |        |          | 30        | 3.2    | warm white              |               | white       |                 | 1              | suspension |
| ITL023W-S | 53   | 1      |       | 1      |          | 12        | 4      | warm white              |               | white       |                 | 1              | transverse |
| ITL027W-S | 53   | 1      |       | 0.67   |          | 30        | 3.2    | warm white              |               | white       |                 | 1              | transverse |
| ITL044W-S | 68   | 1.42   |       | 4.65   |          | 115       | 19.6   | warm white              |               | white       |                 | 2              | transverse |
| ITL046    | 63   | 0.82   | 0.7   |        |          | 30        | 3.4    | pure white              |               | white       |                 | 1              | suspension |
| ITL062W-S | 69   | 1.5    |       | 5      |          | 116       | 22     | warm white              |               | gold        |                 | 2              | transverse |
| ITL063W-S | 69   | 1.2    |       | 6      |          | 210       | 37     | warm white              |               | gold        |                 | 2              | transverse |
| ITL064W-S | 69   | 1      |       | 3.5    |          | 114       | 23     | warm white              |               | gold        |                 | 2              | transverse |
| ITL081W-S | 53   | 1      |       | 0.85   |          | 4         | 2      | warm white              |               | white       |                 | 1              | transverse |
| ITL113W   | 46   | 0.7    |       | 4      |          | 110       | 15.6   | warm white              | slowflash     | warm white  | gold            | 2              | transverse |
| ITL114W   | 46   | 0.9    |       | 4      |          | 130       | 18.6   | warm white              | slowflash     | warm white  | gold            | 2              | transverse |
| ITL115    | 63   | 0.5    | 0.5   |        |          | 16        | 4      | pure white              |               |             |                 | 1              | suspension |
| ITL115W   | 63   | 0.5    | 0.5   |        |          | 16        | 4      | warm white              |               |             |                 | 1              | suspension |
| ITL116W   | 69   | 1.18   |       | 6      |          | 168       | 27     | warm white              |               | gold        |                 | 2              | transverse |
| ITLG111W  | 72   | 0.8    | 0.8   | 0.18   |          | 16        | 4      | warm white              |               |             |                 | 2              | suspension |
| ML015R-S  | 71   | 1      |       | 1      |          | 80        | 10     | red                     |               |             |                 | 1              | wall       |
| ML015RW-S | 71   | 1      |       | 1      |          | 80        | 10     | warm white              |               |             |                 | 1              | wall       |
| ML015W-S  | 71   | 1      |       | 1      |          | 80        | 10     | warm white              |               |             |                 | 1              | wall       |
| ML016R-S  | 71   | 2      |       | 2      |          | 440       | 17.6   | red                     |               |             |                 | 1              | wall       |
| ML016RW-S | 71   | 2      |       | 2      |          | 440       | 17.6   | warm white              |               |             |                 | 1              | wall       |

| Code      | Page | Height | Width | Length | Diameter | Power (W) | Weight | Led colour | Animation               | Flash color | Bioprint colour | No of elements | Mounting |        |
|-----------|------|--------|-------|--------|----------|-----------|--------|------------|-------------------------|-------------|-----------------|----------------|----------|--------|
| ML016W-S  | 71   | 2      |       |        |          | 2         |        |            |                         |             |                 |                | 1        | wall   |
| ML017R-S  | 71   | 0.8    |       |        |          | 2         |        |            |                         |             |                 |                | 1        | wall   |
| ML017RW-S | 71   | 0.8    |       |        |          | 2         |        |            |                         |             |                 |                | 1        | wall   |
| ML017W-S  | 71   | 0.8    |       |        |          | 2         |        |            |                         |             |                 |                | 1        | wall   |
| ML018R-S  | 71   | 4      | 0.66  | 3.37   |          | 440       | 183    | red        |                         |             |                 |                | 4        | wall   |
| ML018RW-S | 71   | 4      | 0.66  | 3.37   |          | 440       | 183    | warm white |                         |             |                 |                | 4        | wall   |
| ML018W-S  | 71   | 4      | 0.66  | 3.37   |          | 440       | 183    | warm white |                         |             |                 |                | 4        | wall   |
| PL312W    | 47   | 1.6    |       | 0.9    |          | 53        | 12     | warm white | slowflash               | warm white  | gold            | 1              | pole     |        |
| PL313W    | 47   | 2      |       | 1      |          | 20        | 10.8   | warm white |                         |             |                 |                | 1        | pole   |
| PL344     | 47   | 0.6    |       |        |          | 0.95      | 10     | 5.2        | pure white              |             |                 |                | 1        | pole   |
| PL344W    | 47   | 0.6    |       |        |          | 0.95      | 10     | 5.2        | warm white              |             |                 |                | 1        | pole   |
| PL345     | 49   | 1.3    |       | 1      |          | 10        | 5.9    | warm white | anim                    |             |                 |                | 1        | pole   |
| PL346W    | 47   | 2.5    |       | 1.42   |          | 23        | 16     | warm white |                         |             |                 |                | 1        | pole   |
| SL005W-S  | 91   | 5      |       |        |          | 3.3       | 100    | 205        | warm white              |             |                 |                | 7        | ground |
| SL012     | 92   | 1.3    | 2.5   |        |          |           | 25     | 8          | pure white              | flash       | pure white      |                | 1        | ground |
| SL012W    | 92   | 1.3    | 2.5   |        |          |           | 25     | 8          | warm white              | flash       | pure white      |                | 1        | ground |
| SL013     | 92   | 2      | 3.5   |        |          |           | 45     | 9          | pure white              | flash       | pure white      |                | 1        | ground |
| SL013W    | 92   | 2      | 3.5   |        |          |           | 45     | 9          | warm white              | flash       | pure white      |                | 1        | ground |
| SL016-S   | 95   | 4.55   | 4.5   |        |          |           | 65     | 130        | warm white              |             |                 |                | 8        | ground |
| SL017W-S  | 95   | 4.8    |       | 5.15   |          |           | 310    | 108        | warm white              |             |                 |                | 7        | ground |
| SL019W-S  | 87   | 2.75   | 2.24  | 3      |          |           | 200    | 190        | warm white              |             |                 |                | 5        | ground |
| SL030R    | 85   | 4      | 0.7   | 6.2    |          |           | 404    | 325        | red                     |             |                 |                | 4        | ground |
| SL032     | 92   | 1.4    | 1.65  |        |          |           | 40     | 7.6        | pure white              |             |                 |                | 1        | ground |
| SL032W    | 92   | 1.4    | 1.65  |        |          |           | 40     | 7.6        | warm white              |             |                 |                | 1        | ground |
| SL033     | 92   | 2.1    | 2.5   |        |          |           | 45     | 8.8        | pure white              |             |                 |                | 4        | ground |
| SL033W    | 92   | 2.1    | 2.5   |        |          |           | 45     | 8.8        | pure white              |             |                 |                | 4        | ground |
| SL034W-S  | 94   | 3      | 4.3   |        |          |           | 241    | 137        | pure white / warm white |             |                 |                | 8        | ground |
| SL035W-S  | 86   | 2      | 0.6   | 2.1    |          |           | 62     | 46         | pure white / warm white | comet       |                 |                | 5        | ground |
| SL036W-S  | 93   | 2.9    | 1     | 1      |          |           | 21     | 31         | warm white              | flash       | pure white      |                | 3        | ground |
| SL037W-S  | 93   | 2.9    | 1     | 1      |          |           | 45     | 51         | warm white              | flash       | pure white      |                | 3        | ground |
| SL041W    | 45   | 3      | 2.4   | 2.4    |          |           | 125    | 103        | warm white              | slowglow    | warm white      | green          | 5        | ground |
| SLED010W  | 88   | 7.5    |       |        |          |           |        |            | warm white              | flash       | pure white      |                | 7        | ground |
| SND016    | 58   | 2.7    |       |        |          |           |        |            | stars / flash           | pure white  |                 |                | 5        | ground |
| SND017    | 58   | 6.25   |       |        |          |           |        |            | stars / flash           | pure white  |                 |                | 5        | ground |

| Code      | Page | Height | Width | Length | Diameter | Power (W) | Weight | Led colour    | Animation             | Flash color | Bioprint colour | No of elements | Mounting   |
|-----------|------|--------|-------|--------|----------|-----------|--------|---------------|-----------------------|-------------|-----------------|----------------|------------|
| SND018    | 58   | 2.7    |       |        | 0.88     | 30        | 25.5   | warm white    | stars / flash         | pure white  |                 | 3              | ground     |
| SND019    | 58   | 6.25   |       |        | 2.2      | 401       | 193    | warm white    | stars / flash         | pure white  |                 | 5              | ground     |
| SND020    | 58   | 2.7    |       |        | 0.88     | 30        | 25.5   | pure white    | stars / flash         | pure white  | frosted blue    | 3              | ground     |
| SND021    | 58   | 5.5    |       |        | 2.5      | 441       | 259    | multicoloured | stars / flash         | pure white  |                 | 32             | ground     |
| SND022    | 56   | 8      |       |        | 2.7      | 474       | 215    | warm white    | stars / flash / comet |             |                 | 13             | ground     |
| SV1001    | 54   | 10     |       |        | 3.43     | 248       | 965    |               |                       |             |                 | 23             | ground     |
| SV1001W   | 54   | 10     |       |        | 3.43     | 248       | 965    |               |                       |             |                 | 23             | ground     |
| SV1201-P  | 54   | 12     |       |        | 4.08     | 440       | 1427   |               |                       |             |                 | 33             | ground     |
| SV1201W-P | 54   | 12     |       |        | 4.08     | 440       | 1427   |               |                       |             |                 | 33             | ground     |
| SV1401    | 54   | 14.36  |       |        | 5.8      | 640       | 4462   |               |                       |             |                 | 49             | ground     |
| SV1401W   | 54   | 14.36  |       |        | 5.8      | 640       | 4462   |               |                       |             |                 | 49             | ground     |
| SV301     | 54   | 3      |       |        | 1.18     | 24        | 41     |               |                       |             |                 | 3              | ground     |
| SV301W    | 54   | 3      |       |        | 1.18     | 24        | 41     |               |                       |             |                 | 3              | ground     |
| SV501     | 54   | 5      |       |        | 1.8      | 60        | 250    |               |                       |             |                 | 6              | ground     |
| SV501W    | 54   | 5      |       |        | 1.8      | 60        | 250    |               |                       |             |                 | 6              | ground     |
| SV801-P   | 54   | 8      |       |        | 2.78     | 200       | 615    |               |                       |             |                 | 17             | ground     |
| SV801W-P  | 54   | 8      |       |        | 2.78     | 200       | 615    |               |                       |             |                 | 17             | ground     |
| TGL140W-S | 65   | 7      | 2.15  | 2.15   |          | 260       | 43.5   | warm white    |                       |             |                 | 1              | transverse |
| TGL150W-S | 51   | 1      |       |        | 1        | 20        | 11     | warm white    |                       |             |                 | 1              | transverse |
| TGL70LW   | 53   | 0.6    |       |        | 0.6      | 30        | 4      | pure white    |                       |             |                 | 1              | transverse |
| TGL70LWW  | 53   | 0.6    |       |        | 0.6      | 30        | 4      | warm white    |                       |             |                 | 1              | transverse |
| TGL71LW   | 53   | 1      |       |        | 1        | 75        | 10.9   | pure white    |                       |             |                 | 1              | transverse |
| TGL71LWW  | 53   | 1      |       |        | 1        | 75        | 10.9   | warm white    |                       |             |                 | 1              | transverse |
| TGL72LW   | 53   | 1.6    |       |        | 1.6      | 165       | 24.8   | pure white    |                       |             |                 | 1              | transverse |
| TGL72LWW  | 53   | 1.6    |       |        | 1.6      | 165       | 24.8   | warm white    |                       |             |                 | 1              | transverse |
| TL153W    | 51   | 1.5    |       | 1.58   |          | 33        | 9      | warm white    |                       |             |                 | 1              | transverse |
| TL154W    | 51   | 0.9    |       | 0.97   |          | 11        | 5      | warm white    |                       |             |                 | 1              | transverse |
| TL169R    | 51   | 1.5    |       | 1.5    |          | 30        | 9      | red           |                       |             |                 | 1              | transverse |
| TL170R    | 51   | 0.8    |       | 0.8    |          | 15        | 2.4    | red           |                       |             |                 | 1              | transverse |
| TL175W-S  | 51   | 1.5    | 1.5   |        |          | 45        | 18.2   | warm white    |                       |             |                 | 1              | transverse |
| TL195W-S  | 51   | 0.9    |       | 1      |          | 15        | 3.8    | warm white    |                       |             |                 | 1              | transverse |
| TL196W-S  | 51   | 1.5    |       | 1.58   |          | 23        | 7      | warm white    |                       |             |                 | 1              | transverse |
| TL199W-S  | 51   | 1.1    |       | 0.63   |          | 8         | 7      | warm white    |                       |             |                 | 1              | transverse |
| TL341W    | 46   | 1.5    |       | 6      |          | 110       | 28     | warm white    |                       |             |                 | 3              | transverse |